



RUS-KIT CO., LTD

ADDRESS IN RUSSIA: RUS-KIT Co., LTD, 109044, MOSCOW, VORONTOVSKAYA STR. 24/6 Building 1.

TEL: +7 495 721-05-41, +7 495 798-00-73

WEB: <http://PVC-KIT.PΦ> E-MAIL: INFO@RUS-KIT.RU

ADDRESS IN CHINA: **Rus-Kit Co., LTD**, XIYITIAO ROAD, NEW-MART B 708, MUDANJIANG CITY, HEILONGJIANG PROVINCE, P.R.CHINA

ZIP CODE: 157000 TEL: **+86-453-626-60-11** FAX: **+86-453-626-60-11**

WEB: <http://WWW.RUS-KIT.CN> E-MAIL: INFO@RUS-KIT.CN

DATA SHEET RK-100

Vulcanized Non-asbestos latex sheet

Application: Vulcanized Non-asbestos latex sheet, it is by vulcanizing, it has smooth face and high density, it can be cut into all kinds of gasket directly.

APPLICATION& PARAMETER:

Used in Automobile, farm machinery, motors, engineering etc. It can be used in oil system and water supply system at temperature +300°C



The maximum pressure: 5,0Mpa.

The maximum temperature: +300°C.

The thickness of material: 0,4mm~3,0mm

MATERIAL CHARACTERISTICS:

PHYSICOMECHANICAL INDICATORS	COMPRESSIBILITY AT PRESSURE OF 35 MPA (%)	20,0±5
	RECOVERY AFTER PRESSURE 35 MPa, NOT LESS (%)	40
	DENSITY:	1,3~1,4g/cm ³
	STABILITY OF A MATERIAL TO INFLUENCE OF TECHNICAL LIQUIDS:	
	1. IN 20# AVIATION OIL WITH THE TEMPERATURE OF 150°C FOR 30 MIN. INCREASE IN A THICKNESS: OIL ABSORPTION:	≤12,0% ≤30,0%
	2. IN WATER 15~30°C FOR 5H: INCREASE IN A THICKNESS:	≤12,0%